



TECHNICAL DATA SHEET

WINDOW, DOOR & SIDING SEALANT

QUAD[®] INVISIBLE

ALL SEASON
FORMULA



Description: OSI QUAD Invisible Window, Door & Siding Sealant all-season formula delivers superior performance on exterior window, door and siding applications. It offers all the great benefits of OSI QUAD in a crystal clear Invisible formula, perfect for finishing work around stone, brick and other fine building materials. OSI QUAD Invisible can be applied to wet or dry surfaces, even at freezing temperatures. OSI QUAD Invisible resists dirt & dust collection, yellowing and water washout, is self-tooling and is paintable with either latex or oil-based paints once cured. OSI QUAD Invisible is composed of elastomeric polymers and high quality synthetic resins. This product offers the superior adhesion characteristics and unmatched elasticity found in high performance sealants. It yields a tough, rubbery seal which resists outdoor weather-related elements like water, oxygen, ozone, heat and UV light. The formula skins over in a short time to resist dirt and dust pickup. It goes on smoothly and has easy cut-off without stringing. When cured, the surface displays a slight sheen similar to some silicone.

Available As:

Item #	Size	Color
1896952	9.5 fl oz (280 ml)	Clear

Features & Benefits:

- Clear "Invisible" Formula
- All-Weather 20°F-120°F Application
- Wet or Dry Surfaces
- Resists Dirt & Dust Collection
- Paintable
- UV and Water Resistant
- Permanently Flexible
- 3" Spout

Recommended For:

Sealing around exterior windows and doors, fiber-cement and vinyl siding, PVC trim, roofing and gutters. It bonds without a primer to most common substrates like cedar, painted or stained woods, fiberglass, vinyl, coated aluminum, steel, metal, brick, stone and concrete.

For Best Results:

- Do not use for sealing expansion joints, including butt joints
- Not compatible with polystyrene foams and polypropylene or polyethylene plastics
- Do not use in applications requiring continuous water immersion
- Do not use as a traffic bearing sealant, on log homes or inside occupied structures
- For best results, should not be used in applications less than 1/4" in depth in order to maintain the integrity of the sealant
- Do not use to fill nail holes
- For joints deeper than 3/8" (9.5 mm), a backing material should be used
- Tooling, feathering or smearing of the sealant is not necessary or recommended

Coverage:

For a 9.5 fl. oz. (280 ml) cartridge:

- A 1/4" (6 mm) bead extrudes approximately 29.1 ft. (8.9 m)
- A 3/8" (9.5 mm) bead extrudes approximately 13.3 ft. (4 m)



TECHNICAL DATA SHEET

Directions:

Tools Typically Required:

Utility knife and caulking gun. For best application results, OSI recommends the use of a high quality caulking gun such as the Albion® B12 Cartridge Gun.

Safety Precautions:

Do not use inside occupied structures. Wear gloves and wash hands after use.

Preparation:

Apply sealant between 20°F (-7°C) and 120°F (49°C). For easier extrusion of sealant at lower temperatures, the material should be kept at room temperature 24 hours prior to use. All surfaces must be clean, dry and free of old caulk, grease, dust, ice, snow, surface water and other contaminants. Insert cartridge into caulking gun, apply moderate pressure in order to break the Break-A-Way Seal™ inside the nozzle. Cut the tip off the cartridge at a 45° angle to desired bead size (3/8" is recommended).

Application:

Using a caulking gun, apply sealant with steady pressure, forcing the sealant into the joint. If the depth of the joint exceeds 3/8" (9.5 mm) the use of a backer rod is recommended. OSI QUAD Invisible will not pop or splatter and will dispense smoothly on extrusion from the cartridge. Tooling of the sealant is not necessary or recommended. Do not feather or smear sealant. Sealant is paintable when fully cured. Full cure may take 7 - 14 days or longer depending on ambient conditions and volume of sealant used. Latex paint is recommended. If using oil based/alkyd paint, a latex primer should be used first.

Clean-up:

Clean tools and uncured sealant residue immediately with mineral spirits or paint thinner. Cured sealant must be carefully cut away with a sharp-edged tool.

Storage & Disposal:

NOT DAMAGED BY FREEZING. Store in a cool, dry place. Take unwanted product to an approved household hazardous waste transfer facility. Hardened material may be disposed of with trash.

Label Precautions:

WARNING! FLAMMABLE. HARMFUL IF INHALED OR SWALLOWED. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION.

WARNING! Contains xylene, mineral spirits and ethylbenzene. **FLAMMABLE.** Vapors may ignite explosively. Do not use or store near heat, sparks or open flame. Do not smoke when using this product. Extinguish all flames and pilot lights and turn off all sources of ignition, including stoves, heaters and electric motors during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation. Use in a well-ventilated area. Avoid breathing vapors. Avoid contact with eyes and skin. Prolonged or repeated exposure may affect the nervous system causing dizziness, headache or nausea. If you experience eye watering, headache or dizziness, leave the area to obtain fresh air. Do not swallow. **FIRST AID:** If swallowed do not induce vomiting, call a physician or Poison Control center immediately. For eye contact flush with water for 15 minutes, call a physician. For skin contact, wash thoroughly with soap and water. If overcome by vapors, get fresh air. **KEEP OUT OF THE REACH OF CHILDREN.**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain, nervous system, liver and kidney damage or may cause cardiac arrhythmia. **INTENTIONAL MISUSE BY DELIBERATELY INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.** If this product is used in an OSHA regulated workplace consult the MSDS before use.

Refer to Safety Data Sheet (SDS) for further information.

Limited Warranty:

This product is warranted to be free from defects in materials when used as directed. Henkel's sole obligation shall be, at its option, to replace or refund the purchase price of product proven to be defective. Henkel makes no other warranty, express or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE and will not be liable for consequential or incidental damages. This limited warranty gives you specific legal rights, which vary from state to state. Henkel may be contacted at 1.800.624.7767 M-F 9:00 am to 4:00 pm ET for warranty assistance.

Disclaimer:

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.



TECHNICAL DATA SHEET



OSI Tougher than the Elements. For Professional Use Only. The Battle will be Fierce.

OSI works side by side with residential builders, contractors and remodeling professionals who use our products everyday on their jobsites. OSI combines this deep understanding with the sophisticated global innovation and manufacturing excellence of Henkel to make the world's best professional-grade caulks, sealants and adhesives.

1-800-624-7767 – Mon-Fri - 9:00a – 4:00p ET

www.ositough.com



OSI Brand is part of the Henkel family of brands. Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care and Adhesive Technologies.

Henkel Corporation - Professional & Consumer Adhesives Headquarters - Rocky Hill, CT 06067

www.henkelna.com

Revision Date:10/09/2014 Supersedes: 07/31/2014 Ref. #: 1634630 Post Date: 07/31/14