



4444 Hunt St. Pryor, OK 74361
Email: info@gaproofing.us
Phone: 918-825-5200
Fax: 918-825-5207

Company Website: GAProofing.us
Dealer Support: GAPdealers.com

ASTM 30 D226 FELT



WE OWN THE PAPER MILL

LOWER PRICING.
LOWER LEAD TIMES.
HIGHER QUALITY RAW MATERIALS.

ASTM 30 D226 FELT

PRODUCT DESCRIPTION

GAP ASTM 30 D226 is an underlayment product that is manufactured from superior quality organic felt that is saturated with asphalt

PRODUCT USE

GAP ASTM 30 D 226 is an underlayment that is applied over the roofing deck before installation of asphalt shingles.

TECHNICAL DATA

ASTM D 226 Type 11

Width of Roll	36"
Roof Coverage per Roll	216 sq ft
Mass of Saturated felt roll	26.0 lbs/ 100 ft sq
Mass of Saturant	15.0 lbs / 100 ft sq
Mass of Desaturated Felt (min)	10.0 lbs / 100 ft sq
Max Ash	10%
Average (min) Breaking Strength	
Machine Direction (with fiber grain)	40 lbf/in
Across Fiber Grain	20 lbf/in
Pliability at 77F When Bend 90 Degrees	3/4" radius
Max. Loss on Heating at 221F	4%

Pallet Size 42" X 48" No. of Rolls per Pallet = 25

MANUFACTURING LOCATIONS:

Pryor, OK

McGregor, TX

Shafter, CA

Jasper, FL